



# StoneGate™ FW-1200 Specifications

## StoneGate™ Firewall and VPN Specifications

Application-Level Inspection, Stateful Inspection, Packet Filtering, Integrated Operating System, Circuit-level firewall with TCP proxy protocol agent

## Firewall Protocol Agents

SIP, FTP, HTTP, H.323, SMTP, SSH, Oracle SQL Net, RSH NetBios Datagram, SunRPC, MS RPC, TFTP, TCP Proxy

## VPN Protocols

IPsec, AES 128, AES 256, DES, 3DES, Blowfish, CAST-128, Twofish, IKE, MD5, SHA-1, PKI (x.509)

## User Authentication

RADIUS, TACACS+, LDAP, Internal LDAP user database

## Management

Remote, centralized enterprise management with StoneGate Management Center, Java-based GUI, encrypted and authenticated connections

### Automatic Upgrades & Updates

Software upgrades and dynamic updates

### Extensive Logging Methods

Direct file archive, advanced filters, traffic recording

### Multiple Alert Methods

E-Mail, SMS (text message), SNMP trap, User-defined scripts

### Efficient Administration

Multiple administration accounts, simultaneous administration, three different administrator levels

## Certifications

Common Criteria EAL4+ (Firewall + VPN + HA v.2.0.5), FIPS 140-2, ICSA Firewall and VPNC IPsec

## Network interfaces

**Full copper version** 8 x 10/100/1000 copper

**Fiber version** 4 x 10/100/1000 copper + 2 x 1000BASE-X fiber

## Performance

**Licensed Firewall Performance** 2 Gbit/s

**Licensed VPN Performance** 400 Mbit/s

**VPN Tunnels** 3 000

**Concurrent Connections** 1 000 000

**Connections/sec.** 15 000

## Features

**High Availability** Active/active firewall clustering with up to 16-nodes, stateful failover (including VPN connections), Server load balancing

**ISP Multihoming** High availability and load balancing between multiple ISPs (including VPN connections)

**Number of protected IPs** Unlimited users

## Connectors

2 x USB ports, serial port, VGA port

## Measurements

**Dimensions (W x H x D)** 1U-19" Telco rack unit, 427 x 43 x 356 mm/16.8" x 1.7" x 14"

**Weight** 6,2 kg/13,7 lbs

## Safety/EMC Certification

FCC, CE, CB

## Other

**Power Supply** 260W, 4A

## Support

**Replacement service** 15 months or 39 months replacement service for non-complying hardware

**Premium Support** 24/7-call logging via Web and phone, two-hour response time, software updates, hardware replacement service

**Basic Support** 8/5-call logging via Web and phone, next business day response time, software updates, hardware replacement service