

StoneGate™ FW-5105

July 2010

StoneGate™



StoneGate™ High Availability Firewall VPN Appliance Datasheet

The StoneGate™ FW-5105 FW/VPN appliance is a firewall solution designed to meet the performance and scalability requirements of data centers, large network central sites, MSP or other operator environments demanding the ultimate 25 Gbps capacity. The FW-5105 has up to four 10 Gbps and eighteen 1 Gbps interfaces providing fast and flexible network segmentation at the perimeter or internal networks requiring high performance.

In these demanding environments StoneGate FW-5105 FW/VPN provides not only reliable data security but also high-availability features, which guarantee continuous information flow. Built-in firewall clustering, server load balancing and the possibility to utilize reserve capacity on overloaded Internet connections guarantee continuous network connectivity.

The robust construction of StoneGate FW-5105 ensures that appliance serves well even in the most demanding environment. Double redundant power supply units (PSUs) together with solid state disk drives and fans ensure that the appliance keeps working even if one PSU goes down.

StoneGate FW-5105 and all other StoneGate appliances offer comprehensive network security with easy configuration and unified management. This ensures an optimized solution for any geographically dispersed enterprise deployment.

STONESOFT

Secure Information Flow

StoneGate™ FW-5105 Specifications



Specifications

General	Application level inspection, stateful inspection, packet filtering, circuit level firewall with TCP proxy protocol agent. Integrated operating system.
Firewall protocol agents	FTP, H.323, HTTP, HTTPS, IMAP4, MS RPC, NetBios Datagram, Oracle SQL Net, POP3, RSH, SIP, SMTP, SSH, SunRPC, TCP Proxy, TFTP
VPN Protocols	IKEv1, IPsec
Encryption	AES-128, AES-256, AES-GCM, Blowfish, DES, 3DES*
Message Digest Algorithms	AES-XCBC-MAC, MD5, SHA-1, SHA-256
Diffie-Hellman	DH group 1, 2, 5 and 14
Authentication	RSA and DSS signatures with X.509 certificates, pre-shared keys, hybrid XAUTH
Compression	IPCOMP Deflate
User Authentication	Internal user database, LDAP, MS Active Directory, RADIUS, TACACS+

Features

High availability	Active/active firewall clustering up to 16 nodes, Active/standby, Stateful failover (including VPN connections), Server loadbalancing, VRRP, Link aggregation, 802.3ad
ISP multihoming	Multi-Link: High availability and load balancing between multiple ISPs including VPN connections
IP address assignment	FW clusters: Static, FW single nodes: static, DHCP, PPPoE, IPv4, IPv6 Services: DHCP Server and DHCP relay
Traffic management, QoS	Guaranteed & Maximum bandwidth, Priorization, Differentiated Services Code Point (DSCP) matching / marking SYN flood limiting, concurrent session limiting
SIP	Allows RTP media streams dynamically, NAT traversal, deep inspection, interoperability with RFC3261 compliant SIP devices
SSL inspection	Decrypts the SSL and inspects the HTTP stream protecting web clients and/or servers
Dynamic multicast routing	IGMP proxy

UTM features

Standard	Deep inspection and IPS fingerprinting for HTTP, IMAP4, POP3, SIP and SMTP
Optional with additional license	Category based Web filtering

Management and Monitoring

Centralized StoneGate Management Center	Enterprise level centralized management, logging and reporting system. See more details from StoneGate Management Center datasheet.
SNMP monitoring	SNMPv1, SNMPv2c and SNMPv3

Certificates

VPNC IPsec	Yes
ICSA Firewall	Yes

Licensed Performance

Firewall throughput	25 Gbps
VPN throughput	5 Gbps
VPN tunnels	30 000
Concurrent connections	4 500 000
Connections/sec	75 000
Number of Protected IPs	Unlimited
Concurrent mVPN Clients	Unlimited
VLANs	Unlimited
Deep inspection throughput	3 Gbps
SSL inspection client/server	250 Mbps/250 Mbps

Hardware

Network interfaces

Ethernet	18 x 10/100/1000 copper, 4 x 10 GBase-SR Ethernet Fiber Ports
----------	---

Connectors

	RS-232 serial console, 4 x USB, VGA
--	-------------------------------------

Measurements

Form factor	3U 19" rack unit
Dimensions (W x H x D)	450 x 132 x 650 mm / 17.7 x 5.2 x 25.6 inches
Net weight	24.8 kg / 54.67 lbs
Gross weight	34.3 kg / 75.62 lbs

Safety/EMC Certifications

	CE, FCC, CB, Gost-R, RoHS
--	---------------------------

Power

Power supply	1 + 1 Redundant 800 + 800 W, AC Input 100-240 VAC, 50-60 Hz
Typical power consumption	300 W

Other

Operating temperature/humidity	10—35°C (50—95°F) 8%—90%, non condensing humidity (RH)
Storage temperature/humidity	-40—70°C (-40—158°F) 5%—95%, non condensing humidity (RH)
MTBF	100 000 hours

Support

Replacement service	15 months or 39 months replacement service for non-complying hardware
Premium support	24/7-call logging via web, email and phone, two-hour response time, software updates, hardware replacement service
Basic support	8/5-call logging via web, email and phone, next business day response time, software updates, hardware replacement service

Product codes**

APP-FW-5105-C1	StoneGate FW-5105 appliance
FP-1Y-WF2-135	Optional one year web filtering subscription for FW-5105